

sys@XR5

Processori	<ul style="list-style-type: none">• Intel Celeron Quad Core
Schede madre	
Memoria	<ul style="list-style-type: none">• 4GB espandibile ad 8GB DDR3L-1600
Storage options	<ul style="list-style-type: none">• 120GB Solid State Drive (SSD)• 500GB Hard Disk Drive (HDD)
Connettività	<ul style="list-style-type: none">• Twelve USB ports<ul style="list-style-type: none">- Three 12v USB 2.0- One 24v USB 2.0- Two PC USB 3.0- Six reserved USB ports for integrated devices• One RJ50 powered serial port with optional 6-port serial expansion• Cash drawer port (12 or 24 volt with dual drawer support)• 10/100/1000MB (Gigabit) Ethernet LAN• HDMI and DisplayPort video outputs
Interfacce utente	<ul style="list-style-type: none">• 15" projected capacitive touchscreen (4:3 aspect ratio, 1024x768 resolution)• Support for 10-finger multi-touch• High bright LED-backlit display• 0 to 110 degree tilt capability for ease of use and installation• Integrated stereo speakers
Opzioni integrate	<ul style="list-style-type: none">• 3-track encrypted MSR• Biometric fingerprint reader (DigitalPersona)• Wireless module (802.11 /Bluetooth)• Front user facing camera
Opzioni display cliente	<ul style="list-style-type: none">• 2 x 20 LED display (integrated and pole mount)• 15" and 10" LED displays (touch and non-touch)
Opzioni sistemi operativi precaricabili	<ul style="list-style-type: none">• Windows® 7 Professional (32-bit or 64-bit)• Windows Embedded POSReady 7 (32-bit or 64-bit)• Windows 10
Altri sistemi operativi supportati	<ul style="list-style-type: none">• SUSE® Linux® Enterprise for Point-of-Service (SLEPOS)
Systems management	<ul style="list-style-type: none">• NCR Command Center• NCR DataGuard enabled• LED Diagnostics• Image Recovery Tool• PXE Network boot• Wake on LAN
Dimensioni	<ul style="list-style-type: none">• 15" terminal with MSR:<ul style="list-style-type: none">- WIDTH 15.45" (392.6 mm)- HEIGHT 13.35" (339.3 mm)- DEPTH 11.75" (298.3 mm)

sys@XR7

Processori	<ul style="list-style-type: none">• Intel® Core™ i5 – 4570TE vPro™ processor• Intel Core i3 – 4330TE processor• Intel Celeron® – 1820TE processor
Schede madre	<ul style="list-style-type: none">• Intel Q87 express chipset• Intel Active Management Technology 9.0 (AMT)• On-board RAID support
Memoria	<ul style="list-style-type: none">• 4GB up to 16GB DDR3 1600
Storage options	<ul style="list-style-type: none">• 80GB solid state drive (SSD)• 500 GB hard disk drive (HDD)• Dual disk drives option (RAID)
Connettività	<ul style="list-style-type: none">• Twelve USB ports<ul style="list-style-type: none">- Three 12v USB 2.0- One 24v USB 2.0- Two PC USB 3.0- Six reserved USB ports for integrated devices• One RJ50 powered serial port with optional 6-port serial expansion• Cash drawer port (12 or 24 volt with dual drawer support)• 10/100/1000MB (Gigabit) Ethernet LAN• HDMI and DisplayPort video outputs• Audio out
Interfacce utente	<ul style="list-style-type: none">• 18.5" projected capacitive touchscreen (16:9 aspect ratio, 1366x768 resolution)• 15" projected capacitive touchscreen (4:3 aspect ratio, 1024x768 resolution)• 15" resistive touchscreen (4:3 aspect ratio, 1024x768 resolution)• Support for 10-finger multi-touch (projected capacitive only)• High bright LED-backlit display• 0 to 110 degree tilt capability for ease of use and installation• Integrated stereo speakers
Opzioni integrate	<ul style="list-style-type: none">• 3-track encrypted MSR• Biometric fingerprint reader (DigitalPersona)• Wireless module (802.11 /Bluetooth)• Front user facing camera
Opzioni display cliente	<ul style="list-style-type: none">• 2 x 20 LED display (integrated and pole mount)• 15" and 10" LED displays (touch and non-touch)
Opzioni sistemi operativi precaricabili	<ul style="list-style-type: none">• Windows® 7 Professional (32-bit or 64-bit)• Windows Embedded POSReady 7 (32-bit or 64-bit)• Windows Embedded POSReady 2009
Altri sistemi operativi supportati	<ul style="list-style-type: none">• Windows Embedded 8.1 Industry Pro Retail capable (64-bit)• Windows 8.1 Pro capable (64-bit)• SUSE® Linux® Enterprise for Point-of-Service (SLEPOS)
Systems management	<ul style="list-style-type: none">• LED Diagnostics• Image Recovery Tool• PXE Network boot• Wake on LAN• Intel Active Management Technology 9.0• Keyboard-Video-Mouse (KVM) Remote Control (with Intel Core i5 vPro processor)• NCR Command Center
Dimensioni	<ul style="list-style-type: none">• 15" terminal with MSR:<ul style="list-style-type: none">- WIDTH 15.45" (392.6 mm)- HEIGHT 13.35" (339.3 mm)- DEPTH 11.75" (298.3 mm)• 18.5" terminal with MSR:<ul style="list-style-type: none">- WIDTH 19.84" (503.9 mm)- HEIGHT 13.80" (350.6 mm)- DEPTH 12.12" (307.8 mm)

